

線材接頭規格種類(FOR IPX 線材)


連接器料號	連接器規格	連接器圖片	連接器料號	連接器規格	連接器圖片
RFC-001	SMA-JC-1.5		RFC-010	SMA-JWC-1.5	
RFC-002	RPSMA-JC-1.5		RFC-011	SMB-JC-1.5	
RFC-003	SMB-KC-1.5		RFC-012	SMA-JWC-1.5	
RFC-004	MCX-JC-1.5		RFC-013	MCX-KC-1.5	
RFC-005	MCX-JWC-1.5		RFC-014	MMCX-JC-1.5	
RFC-006	MMCX-JWC-1.5		RFC-015	MMCX-KC-1.5	
RFC-007	BNC-JC-1.5		RFC-016	BNC-KY-1.5	
RFC-008	TNC-JC-1.5		RFC-017	TNC-KYC-1.5	
RFC-009	N-JC-1.5		RFC-018	N-KYC-1.5	
RFC-038	RPSMA-KYC-1.5		RFC-039	SMA-KYC-1.5	
RFC-040	IPX		RFC-024	SL16-JC-3	

連接器料號	連接器規格	連接器圖片	連接器料號	連接器規格	連接器圖片
RFC-019	SMA-JC-3		RFC-030	BNC-J5	
RFC-020	SMA-KYC-3		RFC-031	SMA-JB2	
RFC-021	BNC - JC - 3		RFC-032	SMA-KYB3	
RFC-022	RPTNC-KC-3		RFC-033	SMA-JWB2	
RFC-023	N-KC-3		RFC-034	MCX-JWB2	
RFC-025	SMA-JWC-3		RFC-035	SMA - JB3	
RFC-026	MMCX-JWC-3		RFC-036	SMA - JWB3	
RFC-027	RPTNC-JC-3		RFC-037	SMA - KYB3	
RFC-028	N-JC-3				
RFC-029	SL16-KC-3				

線材規格種類

線材料號	線材規格	線材圖片
RFL-001	RG174	
RFL-002	RG316	
RFL-003	RG316	
RFL-008	1.13 Gray	
RFL-00a	1.13 Gray open	
RFL-00b	RG178 open	
RFL-004	SYV-50-3 RG58	
RFL-005	SYV-50-5	
RFL-006	086 RG405 半鋼半柔2號線	
RFL-007	141 RG402 半鋼半柔3號線	

線材比較表

		電容值 (pF/m)	阻抗 (ohm)	傳輸速度 (%)	最小彎曲半徑 (mm)	工作電壓 (VMS)	工作溫度 (攝氏)°C
RG174		101.5	50	66	10	1500	-20~+80
RG316		96.45	50	70	13	1200	-55~+200
RG316		96.45	50	70	13	1200	-55~+200
1.13 Gray		95.6	50	70	4	1000	-55~+200
1.13 Gray open		95.6	50	70	4	1000	-55~+200
RG178 open		94.65	50	70	10	1000	-55~+150
SYV-50-3 RG58		104	50	66	35.5	1600	-20~+70
SYV-50-5		104	50	66	72	1~6000	-20~+70
086 RG405 半鋼半柔2號線		95.1	50	61	7.63	1900	-55~+125
141 RG402 半鋼半柔3號線		101.05	50	66	12.5	1900	-20~+80